



**E22H** 

## KWUNPHI—

## The Advocator of High Standard Clean Quality

Dry Brushing		
0~15°		
-20~80℃		
-20~50℃		
40mm		
40mm		
water Washing Angle		
62~74 km/h Fresh Gale		
( IP 55		

Project		
PV panel Angle*		
PV panel Surface Temp.		
Environment Temp.★		
PV panel Gap		
PV Height Difference		
Rainfall		
Wind Power		
IP Rating		

0~10°		
0~80℃		
0~50℃		
40mm		
20mm		
25~50 mm Light Rain		
29~38 km/h Fresh Breeze		
IP 55		

<sup>\*</sup> PV panel angle data ultimately depends on the characteristics of the contaminant. ( $\Rightarrow$  Shenzhen Kwunphi reserves the right to interpret the data )

## Kwun E22H Technical Specification

	<u> </u>		
	Based on TianyunOS Operating System		
	Based on Glass vSLAM Visual Navigation Technology		
Technology	Based on Goodzenn Path Planning Technology		
9,	Based on Ai-KWUN Operating Plat	form	
	Based on OTA-KWUN Operating Platform		
Life & Endurance	Design Life:	6 years	
	Warranty(whichever comes first):	1 year or 2400 hours	
	Battery Capacity:	15Ah	
	The Battery Life*:	4.5 hours	
	Charging Time: 3 hours		
	8 Hours Battery Life: Replace The Battery Every 4.5 hours		
	Dust (adhesion ≤10 <sup>-6</sup> N) :	≥99%	
Ability to Clean	Dust Accumulation (adhesion ≤10		
	Dried Guano (adhesion $\leq 10^{-2}$ N): $\geq 85\%$		
		 ≥450m²/h	
	Cleaning Efficiency:	/450m²/n	
Shape	Body Size* (without brushes):	585*560*250mm	
	Body Weight* (without brushes):	19.75kg	
	Brush Length* (detachable):	936mm (D type)	
	Brush Weight*:	5.7kg & 4.9kg (D type)	
	Number of Rolling Brushes:	2	
	Maximum of Single Central	24 sets	
	Maximum of Single Control:		
	Roof RECO Maximum Number Operate: 4 sets		
	RECO Maximum Number Operate on Slopes: 4 sets		
_	Software Upgrade:	OTA Vari	
Mani- pulation	Work at Night	Yes	
	View Logs in Real Time:	Yes	
	UAV Retraction:	Yes	
	Unmanned on Approach Bridge: Yes		
	APP Control Remotely:	Yes	
	Remote Control:	Yes	
	Breakpoint Continuation:	Yes	
	Adjust the Brush Speed:	Yes	
	Rated Brush Speed:	120r/min	
Security	Working Mode: Autono	mous Work; Mobile APP	
	Positioning Mode:	Al Semantic Vision	
	Positioning Accuracy:	≤10mm	
	Steering Mode: High Precision Adsorption Steering Mechanism		
	Anti-fall Protection: Al Semantic Vision + Ultrasonic		
	Track Self-cleaning + High Precision		
		_	
	Protection Rate :	IP65	
	Microcrack Certificate:	Certificate Issued by BV	

<sup>\*</sup> Battery life may vary due to different situation, loads, battery consumptions and other factors. \* Weight and size of robots may vary slightly due to the change of suppliers.