



KWUNPHI—

The Advocator of High Standard Clean Quality

| Dry Brushing | | |
|-----------------------|--|--|
| 0~15° | | |
| -20~80℃ | | |
| -20~50℃ | | |
| 40mm | | |
| 30mm | | |
| water Washing Angle | | |
| 62~74 km/h Fresh Gale | | |
| IP 55 | | |

| Project | | |
|------------------------|--|--|
| PV panel Angle* | | |
| PV panel Surface Temp. | | |
| Environment Temp.★ | | |
| PV panel Gap | | |
| PV Height Difference | | |
| Rainfall | | |
| Wind Power | | |
| IP Rating | | |
| | | |

| Water Washing | | |
|-------------------------|--|--|
| 0~10° | | |
| 0~80℃ | | |
| 0~50℃ | | |
| 40mm | | |
| 25mm | | |
| 25~50 mm Light rain | | |
| 29~38 km/h Fresh Breeze | | |
| IP 55 | | |

Kwun E32H Technical Specification

| | Passed on TignyunOC Operating Cur | 2+0.02 | |
|---------------------|--|--|--|
| - | Based on TianyunOS Operating System | | |
| Technology | Based on Glass vSLAM Visual Navigation Technology | | |
| | Based on Goodzenn Path Planning Technology | | |
| - | Based on Ai-KWUN Operating Platform | | |
| | Based on OTA-KWUN Operating Plo | attorm | |
| Life & Endurance | Design Life: | 6 years | |
| | Warranty(whichever comes first): | 1 year or 2400 hours | |
| | Battery Capacity: | 15Ah | |
| | The Battery Life*: | 4 hours | |
| | Charging Time: 3 hours | | |
| | 8 Hours Battery Life: Replace Th | ne Battery Every 4 hours | |
| Ability to Clean | Dust (adhesion ≤10 ⁻⁶ N) : | ≥99% | |
| | Dust Accumulation (adhesion ≤10 | ⁻⁴ N): ≥95% | |
| | Dried Guano (adhesion ≤10-2N): | ≥85% | |
| | Cleaning Efficiency: | ≥650m²/h | |
| Shape | Dody Cinct (with out househoo) | 585*560*250mm | |
| | Body Size* (without brushes): | | |
| | Body Weight* (without brushes): | 23.85kg | |
| | Brush*(detachable): | 7.2kg (B type) | |
| | Brush and Water Branch*: Brush length*: | 8.3kg (B type) 1285mm (B type) | |
| | Brush length . | 120311111 (B type) | |
| Mani- pulation | Maximum of Single Control: | 24 sets | |
| | Roof RECO Maximum Number Operate: 4 sets | | |
| | RECO Maximum Number Operate o | | |
| | Software Upgrade: | OTA | |
| | Work at Night | Yes | |
| | View Logs in Real Time: | Yes | |
| | UAV Retraction: | Yes | |
| | Unmanned on Approach Bridge: | Yes | |
| | APP Control Remotely: | Yes | |
| | Remote Control: | Yes | |
| | Breakpoint Continuation: | Yes | |
| _ | Adjust the Brush Speed: | Yes | |
| | Rated Brush Speed: | 140r/min | |
| | Ratea Brash opeca. | 160r/min | |
| | • | mous Work; Mobile APP | |
| | • | mous Work; Mobile APP Al Semantic Vision | |
| | Working Mode: Autonor | mous Work; Mobile APP | |
| | Working Mode: Autonor Positioning Mode: Positioning Accuracy: | mous Work; Mobile APP Al Semantic Vision ≤10mm | |
| Security | Working Mode: Autonor Positioning Mode: Positioning Accuracy: Steering Mode: High Precision Ad Anti-fall Protection: Al Sema | mous Work; Mobile APP Al Semantic Vision ≤10mm dsorption Steering Mechanismentic Vision + Ultrasonic | |
| Security | Working Mode: Autonor Positioning Mode: Positioning Accuracy: Steering Mode: High Precision Ad Anti-fall Protection: Al Sema | mous Work; Mobile APP Al Semantic Vision ≤10mm dsorption Steering Mechanismentic Vision + Ultrasonic | |
| Security | Working Mode: Autonor Positioning Mode: Positioning Accuracy: Steering Mode: High Precision Ad Anti-fall Protection: Al Sema | mous Work; Mobile APP Al Semantic Vision ≤10mm dsorption Steering Mechanism | |

^{*} Battery life may vary due to different situation, loads, battery consumptions and other factors. * Weight and size of robots may vary slightly due to the change of suppliers.